

# Baquacil Sanitizer and Algistat Directions for Use

## Important information

Baquacil sanitizer and algistat is not compatible with chlorine-based products.

Consult Your Authorized Baquacil Dealer for Guidance

### **Making The Switch From Chlorine to Baquacil Sanitizer & Algistat**

1. Neutralize Chlorine: Start by Using Baquacil Chlorine Neutralizer or Baquacil Oxidizer (1 Gallon) per 10,000 Gallons).
2. Filter Overnight: After Allowing Your Pool Filter System To Operate Overnight Recheck Your Chlorine Levels. If Chlorine Still is in the Swimming Pool Repeat The Neutralization Process.
3. For Plaster Pools: Add 1 ¼ lbs. of Baquacil Metal Control Per 10,000 Gallons.

### **Starting with a Freshly or Refilled Swimming Pool**

1. First Backwash or Clean Your Pool Filter. Additionally, Adjust pH Levels to 7.2 - 7.8
2. Next Add a Single ½ Gallon Bottle of Baquacil Sanitizer and Algistat per 10,000 Gallons of Water to Reach 50 ppm.
3. After Twenty-Four Hours Retest and Adjust Baquacil Sanitizer and Algistat Levels (Adjust as Needed).

### **Weekly Swimming Pool Maintenance**

- Maintain a Level of 50 ppm of Bauqacil Santizer and Algistat (Do not allow it to drop below 30 ppm).
- If Levels Drop Below 10 ppm or More, add 1 Pint per 10,000 Gallons.
- In Addition Check pH and Baquacil Sanitizer and Algistat Levels Weekly.

### **Kiddie Pool Treatment**

1. Fill the Kiddie Pool with Fresh Water.
2. Check the Dosing Chart Below and Add The Correct Dose of Baquacil Sanitizer and Algistat.
3. Test the kiddie pool water after 1 minute the color should be in the "OK" range.
4. Drain and refill the kiddie pool weekly, scrubbing pool sides before refilling.

### **Hot Tub and Spa Treatment**

1. **This product is incompatible with chlorine and bromine**
2. Drain, clean, and refill the hot tub or spa before use.
3. Add 1 oz. of Baquacil Sanitizer & Algistat per every 150 gallons to reach 50 ppm.
4. Allow the spa water to circulate for 15 minutes.

### **Weekly Spa Maintenance**

- Maintain a sanitizer level between 30-50 ppm
- To increase Baquacil Sanitizer and Algistat levels 10 ppm add 0.2 oz per 150 gallons of spa water.

### Automated Dosing System Users

- Connect a ½ gallon bottle of Baquacil Sanitizer and Algistat to your system.
- An initial dose of 64 fl. oz. per 10,000 gallons for 50 ppm is recommended.
- For weekly maintenance test and maintain a level of 30 - 50 ppm.
- Monthly maintenance requires taking a water sample to your local dealer.
- At the end of the season disconnect the system and safely store any remaining Baquacil Sanitizer an Algistat

### Baquacil Sanitizer and Algistat Dosing Chart

Pool Volume (Gallons)	Baquacil Sanitizer & Algistat (Teaspoons)	Baquacil Sanitizer & Algistat (Tablespoons)	Baquacil Sanitizer & Algistat (Ounces)
25	1	1/3	1/6
75	3	1	½
100	4	1 1/3	2/3
150	6	2	1
200	8	2 2/3	1 1/3
250	10	3 1/3	1 2/3
300	12	4	2
350	14	4 2/3	2 1/3

**For Further Troubleshooting or Additional Guidance, Contact Your Authorized Baquacil Dealer**